

SETTINGLIST FORK

OEM

Modellbezeichnung / Model description

KTM 450 SX-F Fact. Ed. / HQV FC 450 Rocks. Ed. /
GG MC 450-F Fact. Ed.

Artikelnummer / Article number	A460C199X406000
-----------------------------------	-----------------

	Fahrer Komfort / driving comfort	STANDARD	Fahrer Sport / driving sport
Druckstufendämpfung (Klicks offen) / compression damping (clicks open)	17	12	7
Zugstufendämpfung (Klicks offen) / rebound damping (clicks open)	23	18	13

Ölmenge Cartridge rechts / oil capacity cartridge right	380	ml
Fettmenge Cartridge links / grease quantity cartridge left	5	g
Ölmenge Außenwerk rechts / oil capacity outertube right	230	ml
Ölmenge Außenwerk links / oil capacity outertube left	230	ml

min/max	180/240	ml	Öl Viskosität / oil viscosity	SAE 4
min/max	180/240	ml	Federweg / fork stroke	310 mm
			Gabellänge / fork length	950 mm

Einstellung / adjustment	Gewicht Fahrer / riders weight	Luftdruck / pressure
Weicher / softer	65-75 kg 143-165 lb	10,7 bar
STANDARD	75-85 kg 165-187 lb	10,9 bar
Härter / harder	85-95 kg 187-209 lb	11,1 bar

Shims Kolben Midvalve / shims piston midvalve			
Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
3	8x12x0.20	1	6x18x4.00
1	8x24x0.20	4	6x18x0.40
1	8x22x0.20	1	6x12x0.15
1	8x20x0.20	1	6x16x0.10
1	8x18x0.20	1	6x18x0.10
1	8x16x0.20	1	6x20x0.10
1	8x14x0.20	1	6x22x0.10
1	8x11x0.40	1	6x24x0.10
1	8x12x0.15	1	6x26x0.10
1	8x14x0.15	2	6x28x0.10
1	8x16x0.15	1	6x26x0.10
1	8x18x0.15	1	6x24x0.10
1	8x20x0.15		
1	8x22x0.15		
1	8x24x0.15		
1	8x26x0.15		
1	8x28x0.15		
7	8x30x0.15		
2	6x9x0.20		

Shims Kolben Basevalve / shims piston basevalve			
Stk / Qty	Druckstufe / compression	Stk / Qty	Zugstufe / rebound
1	6x25x4.00	1	6x18x4.00
1	6x18x0.20	1	6x10x0.20
1	6x20x0.15	1	48601841
1	6x22x0.15		
1	6x24x0.15		
1	6x26x0.15		
1	6x28x0.15		
1	6x30x0.15		
1	6x25x0.10		
12	6x30x0.10		

Basevalve Baugruppe Nr.: / basevalve assembly no.:	Federrate & -länge / spring rate & length	16 N/mm
48602049S5		114 mm